

Main Specifications

Brightness	200 ANSI Lumens
Contrast Ratio (FOFO)	100,000:1
Speaker	5W Chamber x 1

All Specifications

Display

Projection System	DLP 3430
Resolution	480p (854 x 480 pixels)
DMD type	0.2"
Brightness	200 ANSI Lumens
Contrast Ratio (FOFO)	100,000:1
Display Color	16.7 Million Colors
Native Aspect Ratio	Native 16:9 (5 aspect ratio selectable)
Light Source	Osram Q9 LED
Light Source Life (Normal/Eco/SmartEco)*	20,000/30,000 hrs (Normal/Eco)

Optical

Throw Ratio	1.3 (35"@1m)
Zoom Ratio	Fixed
Keystone Adjustment	ID, Vertical \pm 40 degrees
Projection Offset	100% \pm 5%
Projection Size (Clear Focus / Maximum)	30"~100"

SoC

OS	Android 7.1.2
----	---------------

Internet

WLAN	IEEE 802.11 a/b/g/n, 2.4G/5G
Antenna	Yes

Audio

Speaker 5W Chamber x 1

Special Feature

Feature Wireless Projection (for iOS/macOS, for Android™, for PC), USB-C™ DisplayPort and Reader, 15° Tiling Lens and Auto Keystone, 3 Hours Battery, Bluetooth Speaker

Compatibility

Resolution Support VGA(640 x 480) to Full HD(1920 x 1080)

Power

Typical Power Consumption 24W(Max)/ 16.7W(Typical)/ 13.1W(Battery)/ 0.5W(Standby)

Standby Power Consumption 0.5W Max. at 100 ~ 240VAC

Power Supply VAC 100 ~ 240 (50/60Hz)

Dimension and Weight

Dimensions (W x H x D) 80mm x 155mm x 80mm

Weight 708g

Operation Condition

Noise Level (Normal/Eco) 29dBA/28dBA

Operating Temperature 0~40°C

Accessories (Standard)

Power Adaptor x1

Plug set (depends on SKU) Yes

USB-C™ wire (for DP alt mode and data transfer) x1

Carry Bag x1

Remote Control w/ Battery (RC model name) x1 (RCI014)

Quick Start Guide Yes

Warranty Card (by region) Yes

HDMI cable HDMI to USB-C adapter x 1

OSD

Language

Arabic/ English/ French/ German/ Hindi/ Japanese/ Korean/
Portuguese/ Simplified Chinese/ Spanish/ Traditional Chinese
(11 Languages)