

CHRISTIE BOXER SERIES

Technical specifications		Christie Boxer 4K30	Christie Boxer 4K20
Image	brightness	<ul style="list-style-type: none"> • Up to 32,500 ISO • 30,000 Center • 29,000 ANSI (typical) 	<ul style="list-style-type: none"> • Up to 22,000 ISO • 20,000 Center • 19,500 ANSI (typical)
	contrast	• 2000:1	• 2000:1
Display	technology	• 3DLP 1.38" 4K DMD	• 3DLP 1.38" 4K DMD
	resolution	• 4K (4096 x 2160)	• 4K (4096 x 2160)
Lamps		• 6 x 450W NSH	• 4 x 450W NSH
Inputs	standard	<ul style="list-style-type: none"> • 2 x 12G-SDI • 1 x HDMI 2.0 • 1 x DisplayPort™ 1.2 • 1 x Fiber (QSFP+) for use with Christie Link Transmitter • HDBaseT 	<ul style="list-style-type: none"> • 2 x 12G-SDI • 1 x HDMI 2.0 • 1 x DisplayPort 1.2 • 1 x Fiber (QSFP+) for use with Christie Link Transmitter • HDBaseT
	optional	<ul style="list-style-type: none"> • Dual 3G SD/HD-SDI input card • Dual Link DVI input card • High Bandwidth Multi-Input Card (HBMIC) • Quad DisplayPort input card • Twin HDMI™ input card • Terra® SDVoE input card 	<ul style="list-style-type: none"> • Dual 3G SD/HD-SDI input card • Dual Link DVI input card • High Bandwidth Multi-Input Card (HBMIC) • Quad DisplayPort input card • Twin HDMI input card • Terra SDVoE input card
	pixel clock	• 1.2Gpx/s - Christie TruLife™ electronics	• 1.2Gpx/s - Christie TruLife electronics
Physical	dimensions	• (LxWxH) 36.77 x 23.39 x 12" (934 x 594 x 305mm)	• (LxWxH) 36.77 x 23.39 x 12" (934 x 594 x 305mm)
	weight	• 160lbs (72.57kg)	• 160lbs (72.57kg)
dBA		• 49dBA	• 49dBA