


RemotePoint®

# Navigator 2.4

INTERLINK  
ELECTRONICS



## RF PRESENTATION REMOTE

50' Range

2.4 GHz Global RF

Perfect for PowerPoint®

[WWW.RPNAV.COM](http://WWW.RPNAV.COM)

# RemotePoint<sup>™</sup> Navigator 2.4 RF PRESENTATION REMOTE

Model: VP4150 North America  
VP4160 Europe

## CONFIDENCE. CONTROL. CREDIBILITY.

- HIDE** When you need the audience to focus on you, hide your presentation with the press of a button. Press again and slides reappear.
- BACK** Return to the previous slide with ease.
- LASER** Highlight your key points with the integrated laser.
- FORWARD** Advance slides with one touch accuracy from up to 50 feet away.



Confidence and credibility are critical to successful presentations. RemotePoint Navigator 2.4 puts slide control discretely in the palm of your hand. The compact size is comfortable to operate and raised icons identify options, even in the dark.

With up to 50 feet of wireless range, Navigator has no line-of-sight issues—allowing you to focus on your audience, not your slides. Every Navigator shares a unique code with its receiver and can communicate on 4 separate channels, preventing interference from other remote controls. The result: confidence, credibility and the peace of mind that comes knowing that every slide will advance reliably, at the moment you command it to.

Not a computer wizard? You don't need to be. Just plug in the USB receiver, pick up the RemotePoint Navigator 2.4 and start winning over the world—one audience at a time.

- ### REMOTE SPECIFICATIONS
- Range: Up to 50 feet (15m)
  - Radio: 64,000 Unique Addresses  
4 Channels
  - Frequency: 2.4GHz
  - Dimensions: 2" x 4" x 1"  
(51mm x 102mm x 25mm)
  - Weight: Less than 5 ounces (140g)
  - Power: 2 AAA batteries
  - Battery Life: 6 months typical
  - Laser: Class II Laser

- ### RECEIVER SPECIFICATIONS
- Interface: USB
  - Dimensions: 13/16" x 3 1/2" x 1/8"  
(21mm x 89mm x 11mm)
  - Weight: Less than 2 ounces (60g)
  - Power: 20 mA

- ### SYSTEM REQUIREMENTS
- USB Capability
  - Windows<sup>®</sup> 98, 2000, Me, XP  
Mac OS 8.0 and higher



Corporate Office:  
546 Flynn Road  
Camarillo, CA 93012 USA  
Phone: (800) 340-1331  
Fax: (805) 484-8989  
www.interlinkelectronics.com

Japan Office:  
4F Shinoda Bldg., 1-10-7 Higashi Kanda  
Chiyoda-Ku, Tokyo 101-0031 Japan  
Phone: 03-3863-6493  
Fax: 03-3863-6442  
www.interlinkelec.co.jp

©2004 Interlink Electronics, Inc.  
P/N 90-23652 Rev. A  
RemotePoint, Interlink Electronics and the six dot logo are trademarks of Interlink Electronics, Inc.  
US and foreign patents pending.

