

Size & Weight

Dimensions (W x H x D)	18.13" x 8.28" x 20.34"
Weight	Approx. 31 lb (14 kg)

Interface

Input and Output Terminals	HDMI (TWO INPUTS)* - Digital RGB/Y Pb/Cb Pr/Cr, IR IN - Minijack, LAN - RJ45, 10Base-T/100BASE-TX, REMOTE - RS-232C, D-sub 9-pin (male), TRIGGER - Minijack, DC 12 V Max. 100 mA, 3D SYNC OUT - Minijack, USB - Type A, DC 5 V, Max. 500 mA *Both HDMI inputs are compatible with HDCP 2.3.
----------------------------	---

Power

Power Consumption	350 W
Power Requirement	AC 100 V to 240 V, 50/60 Hz
Acoustic noise	26 dB *The value depends on the environment or how the projectors are used.

Eco and energy saving

Power Consumption (Standby Mode)	0.3 W (When "Remote Start" is set to "Off")
Power Consumption (Networked Standby Mode)	0.5 W (LAN) (when "Remote Start" is set to "On") When a LAN terminal is not connected, it becomes a low power consumption mode (0.5 W)

Standby Mode Activated

After about 10 Minutes

Accessibility

Screen Reader Yes

Display

Display Resolution 720 x 576/50p, 720 x 480/60p, 1280 x 720/50p, 1280 x 720/60p, 1920 x 1080/50i, 1920 x 1080/60i, 1920 x 1080/24p, 1920 x 1080/50p, 1920 x 1080/60p, 1920 x 1080/120p, 3840 x 2160/24p, 3840 x 2160/25p, 3840 x 2160/30p, 3840 x 2160/50p, 3840 x 2160/60p, 4096 x 2160/24p, 4096 x 2160/25p, 4096 x 2160/30p, 4096 x 2160/50p, 4096 x 2160/60p

Display System 4K SXRD™ panel, projection system

Light source Laser diode

Picture processor X1™ Ultimate for projector