

Key Features

SuperColor: Amazing Color Accuracy | Large Images In Small Spaces |
3,500 Lumen Brightness | HDMI Input & Powered USB | Long Lamp Life




Product Description


The ViewSonic® PS501X price-performance short throw projector features 3,500 lumens, native XGA 1024 x 768 resolution, a user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. A short throw lens with a 0.61 throw ratio offers large projection images for smaller rooms. The PS501X also features HDMI and VGA connectivity, and a RS232 control port. An energy-saving DynamicEco® feature reduces power consumption by up to 70%, and extends the lamp life up to 15,000 hours. With advanced audiovisual features, flexible connectivity options, and an affordable price, the PS501X is ideal for use in education and small business environments.



- | | |
|---------------------|-----------------|
| 1. Menu Controls | 7. HDMI |
| 2. Elevation Feet | 8. Audio In |
| 3. Zoom Ring | 9. Audio Out |
| 4. IR Remote Sensor | 10. AC In |
| 5. Projection Lens | 11. Monitor Out |
| 6. VGA In (x2) | 12. USB Mini |




- | | |
|---------------------------|-----------------|
| 13. Video | 11. Monitor Out |
| 14. USB 2.0 Type A | 12. USB Mini |
| 15. Kensington® Lock Slot | |
| 16. RS232 | |



1024 x 768
RESOLUTION



3,500 ANSI
LUMENS



0.61
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP Lamp
Resolution Type:	XGA (1024x768)
Resolution:	1024 x 768
Brightness (Lumens):	3,500 ANSI
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	2.4 - 7.3 ft / 0.7 - 2.2 m
Throw Ratio:	0.61
Keystone:	Vertical (+/- 40°)
Lens:	Fixed Zoom
Light Source (watt):	190
Light Source Life, Normal (hours):	5000
Light Source Life, Dynamic Eco-Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	22,000:1
Aspect Ratio:	4:3

Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

Compatibility:

PC Resolution (max):	1920 x 1080
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1080
Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4 In(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), Mini USB(1)

Audio:

Internal Speakers:	2W (x1)
--------------------	---------

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	260W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	5.7
Gross (lbs):	7.2

Weight (metric):

Net (kg):	2.6
Gross (kg):	3.3

Dimensions (imperial) (WxHxD):

Packaging (in.):	14.4 x 7.4 x 11.8
Physical (in.):	11.5 x 4.5 x 9.3

Dimensions (metric) (WxHxD):

Packaging (mm):	365.0 x 188.0 x 300.0
Physical (mm):	292.0 x 115.0 x 236.0

General:

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: PS501X projector, power cable, VGA cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907958119

Accessories:

HB10B, PGD-350, PJ-IWBADP-006, PJ-IWBADP-008, PJ-SCW-1001W, PJ-VTOUCH-10S, PJ-WMK-007, PJ-WMK-305, PRJ-EE-07-03, PRJ-EEEW-07-01, PRJ-EEEW-07-02, PRJ-EW-07-01, PRJ-EW-07-02, RLC-108, VC10, VCB10