




Key Features

Two Monitors in a Single Package | SuperClear IPS Panel Technology |
 Environmentally Friendly Packaging | Frameless design | Versatile
 Connectivity



Product Description


The ViewSonic® VA2456-mhd_H2 dual monitor pack delivers an efficient end-to-end enterprise experience. From easy installation, to recycling, to long-term reliability, this dual monitor solution reduces the total cost of ownership beyond the initial purchase price. Sold as a dual pack of monitors without monitor stands, the VA2456-mhd_H2 ships in biodegradable packaging to minimize recycling costs and waste. Standard VESA-compatible mounting offers easy dual-screen installation, while a 3-sided thin bezel design provides a seamless viewing experience for multi-monitor setups. SuperClear® IPS panel technology delivers wide-angle viewing and incredibly vivid colors. Extensive connectivity options include VGA, HDMI, and DisplayPort so that you can connect to a variety of HD and analog devices – today and tomorrow.



24"
DISPLAY



IPS
PANEL



1920 x 1080
RESOLUTION

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	IPS
Resolution:	1920 x 1080
Resolution Type:	HD (1920x1080)
Static Contrast Ratio:	1,000:1
Dynamic Contrast Ratio:	50,000,000:1
Light Source:	LED
Brightness:	250 cd/m2
Colors:	16.7M
Color Space Support:	8-Bit
Aspect Ratio:	16:9
Response Time (Typical GTG):	14ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30,000
Panel Surface:	Anti-glare, Hard coating (3H)

Compatibility:

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080

Connector:

3.5mm Audio In(1), 3.5mm Audio Out(1), VGA(1), HDMI 1.4 In(1), Display Port(1)

Audio:

Internal Speakers:	2W (x2)
--------------------	---------

Power:

Eco Mode (Conserve):	14W
Eco Mode (optimized):	18W
Consumption (typical):	22W
Consumption (max):	31W
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.5W
Power Supply:	Internal

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Controls:

Physical Controls:	Key Buttons 1, 2, 3, 4, 5, 6 (Power)
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%

Mount:

VESA Compatible:	100 x 100 mm
------------------	--------------

Video Signal:

Frequency Horizontal:	HDMI: 15 ~ 83KHz, DisplayPort: 24 ~ 83KHz
Frequency Vertical:	HDMI: 50 ~ 75Hz, DisplayPort: 50 ~ 75Hz

Video Input:

Digital Sync:	TMDs for HDMI, PCI-E for DisplayPort
---------------	--------------------------------------

Weight (imperial):

Net (lbs):	15.4
Gross (lbs):	22.7

Weight (metric):

Net (kg):	7.0
Gross (kg):	10.3

Dimensions (imperial) (WxHxD):

Packaging (in.):	24.1 x 16.3 x 7.8
Physical (in.):	21.3 x 12.8 x 1.9

Dimensions (metric) (WxHxD):

Packaging (mm):	611.0 x 414.0 x 199.0
Physical (mm):	539.8 x 324.6 x 49.3

General:

Regulations: cULus, FCC-B, ICES003, Energy Star 7.0, EPEAT, Mexico Energy, MX-CoC

PACKAGE CONTENTS: 2x LCD Displays, 2x Power Cable, 1x HDMI Cable, 1 x Display Port Cable, 2x Audio Cable, 2x Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907994551

Accessories:

CB-00009950, CB-00010555, CB-00010684, CB-00010958, LCD-DMA-001, LCD-DMA-002, LCD-WMK-001, ViewSplit