




Key Features

SuperClear® IPS Panel Technology | Frameless Design | Versatile Connectivity | Full HD 1080p resolution | Optimized View Settings



Product Description


With flexible connectivity, wide-angle viewing, and amazing screen performance, the ViewSonic® VA2459-smh delivers solid multimedia features and a sleek design at a great value. Featuring SuperClear® IPS panel technology, the VA2459-smh delivers stunning brightness and contrast at nearly any viewing angle. A minimalistic design, edge-to-edge screen, and frameless bezel make this an ideal monitor for nearly seamless multi-screen setups. Whether for working at the office, or enjoying entertainment at home, the VA2459-smh also features an HDMI port for flexible connectivity to PCs, laptops, gaming consoles, and other multimedia devices. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies, makes the VA2459-smh a great overall value choice.



24"
DISPLAY



IPS
PANEL



1920 x 1080
RESOLUTION

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	IPS
Resolution:	1920 x 1080
Static Contrast Ratio:	1,000:1
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	250 cd/m2
Colors:	16.7M
Color Space Support:	6-Bit+ HI-FRC
Aspect Ratio:	16:9
Response Time (Typical GTG):	14ms
Response Time (GTG w/OD):	7ms
Viewing Angles:	178° horizontal, 178° vertical
Panel Surface:	Anti-glare, Hard coating (3H)

Compatibility:

PC Resolution (max):	1920 x 1080
Mac® Resolution (max):	1920 x 1080

Connector:

3.5mm Audio In(1), 3.5mm Audio Out(1), VGA(1), HDMI 1.4 In(1)

Audio:

Internal Speakers:	2W (x2)
--------------------	---------

Power:

Eco Mode (Conserve):	14W
Eco Mode (optimized):	18W
Consumption (typical):	21W
Consumption (max):	28W
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.5W

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Controls:

Physical Controls:	1, 2, 3, 4, 5, Power
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%

Mount:

VESA Compatible:	100 x 100 mm
------------------	--------------

Video Signal:

Frequency Horizontal:	24 ~ 83KHz
Frequency Vertical:	50 ~ 76Hz

Video Input:

Digital Sync:	TMDS
---------------	------

Ergonomics:

Tilt (Forward/Back):	5° / 22°
----------------------	----------

Weight (imperial):

Net (lbs):	7.2
Net Without Stand (lbs):	6.2
Gross (lbs):	10.8

Weight (metric):

Net (kg):	3.3
Net Without Stand (kg):	2.8
Gross (kg):	4.9

Dimensions (imperial) (WxHxD):

Packaging (in.):	24.1 x 18.0 x 6.3
Physical (in.):	21.3 x 15.4 x 7.9
Physical Without Stand (in.):	21.3 x 12.8 x 1.8

Dimensions (metric) (WxHxD):

Packaging (mm):	613 x 457 x 160
Physical (mm):	540.4 x 389.9 x 200
Physical Without Stand (mm):	540.4 x 323.8 x 45.5

General:

Regulations: cULus, FCC-B, ICES003, Energy Star, Mexico-CoC, Mexico Energy
 PACKAGE CONTENTS: LCD Display, Power Cable , VGA Cable, Audio Cable , Quick Start Guide
 Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.
 Warranty: Three-year limited warranty on parts, labor and backlight
 UPC: 766907888935

Accessories:

CB-00008948, CB-00009950, LCD-EE-24-03, LCD-EEEW-24-01, LCD-EEEW-24-02, LCD-EW-24-01, LCD-EW-24-02, LCD-EW-24-03, VSPF2380